



*Antenna Factory, Inc.*

www.antennafactory.com

Toll Free: 877-288-9112 Fax: 847-584-9952

BPD1710-14.5-90



## Specifications:

<b>Frequency Range</b>	1710-1880 MHz
<b>Gain</b>	14.5 dBi
<b>Horizontal Beamwidth</b>	90°
<b>Vertical Beamwidth</b>	14°
<b>F/B Ratio</b>	≥ 23 dB
<b>Intermodulation IM3</b>	≤ -110 dBm
<b>VSWR</b>	≤ 1.5
<b>Nominal Impedance</b>	50 ohm
<b>Polarization</b>	Vertical
<b>Maximum Input Power</b>	200 W
<b>Lightning Protection</b>	DC Ground
<b>Connector Place</b>	Bottom
<b>Connector</b>	N Female or 7/16 DIN Female
<b>Dimension</b>	700mm × 160mm × 60mm / 2.30ft × 0.52 ft × 0.20 ft
<b>Weight</b>	6 kg / 13.23 lb
<b>Rated Wind Velocity</b>	216 km/h / 135 mph
<b>Radiating Elements Material</b>	Brass
<b>Back Panel Material</b>	Passivated Aluminum
<b>Radome Material</b>	Fiberglass
<b>Mounting Mast Diameter</b>	φ 40 – 89 mm / φ 1.57 – 3.50 in

Every effort is made to insure the product specifications are complete and accurate.  
However, omissions, changes to product specifications and design changes may occur without notice.