



Antenna Factory, Inc.

www.antennafactory.com

Toll Free: 877-288-9112 Fax: 847-584-9952

BPD800-15-65T6



Specifications:

| | |
|---------------------------------|--|
| Frequency Range | 824-896 MHz |
| Bandwidth | 72 MHz |
| Gain | 15.5 dBi |
| VSWR | ≤ 1.5 |
| Nominal Impedance | 50 Ω |
| Polarization | $\pm 45^\circ$ |
| Maximum Power | 500 W |
| Electrical Downtilt | 6 $^\circ$ |
| Dimensions | 1756mm \times 286mm \times 113mm / 5.76 ft \times .94 ft \times .37 ft |
| Rated Wind Velocity | 216 km/h / 135 mph |
| Connector | 2 \times N Female, 2 \times 7/16DIN Female |
| Lightning Protection | DC Ground |
| Weight | 12.5 kg / 27.56 lb |
| Cross-Polarization | > 15 dB |
| IM3 | ≤ -107 dBm |
| Horizontal Beamwidth | 65 $^\circ$ |
| Vertical Beamwidth (3dB) | 16 $^\circ$ |
| Isolation | > 28 dB |
| F/B Ratio | ≥ 25 dB |
| Radome Material | Fiberglass, UV-resistance ABS |

Every effort is made to insure the product specifications are complete and accurate.
However, omissions, changes to product specifications and design changes may occur without notice.