



Antenna Factory, Inc.

www.antennafactory.com
Toll Free: 877-288-9112 Fax: 847-584-9952

BPD890-15.7-60



Specifications:

Frequency Range	806-896 MHz
Gain	15.7 dBi
3D Beamwidth Vertical Plane	12°
3d Beamwidth Horizontal Plane	60°
F/B Ratio	≥ 30dB
VSWR	≤ 1.35
Nominal Impedance	50 ohm
3D Beamwidth	± 45
Maximum Input Power	500 W
Lightning Protection	All metal parts grounded
Connector	N Female or 7/16 DIN Female
Dimension	1538mm × 316mm × 127mm / 5.05 ft × 1.05 ft × .42 ft
Weight	11.3 kg / 24.91 lb
Rated Wind Velocity	216 km/h / 135 mph
Radiating Elements Material	Brass
Back Panel Material	Passive Plane
Radome Material	Fiberglass
Mounting Mast Diameter	φ 40 – 89 mm / φ 1.57 – 3.50 in
Intermodulation IM3	≤ -110 dB
Isolation	≥ 30dB
Electrical Downtilt	Adjustable from 0 to 6°

Every effort is made to insure the product specifications are complete and accurate.
However, omissions, changes to product specifications and design changes may occur without notice.